



LED PANEL 60609

NASSLI
LED LAMP

Product .: LED Panel 60609

Item No.: NSL-LPLG2-60609-30WATT-4000K

Application

It can be widely used in decoration, shopping malls, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting Rooms, Factories, Theater, Cinemas, Kitchens and Corridor etc...

Technical Data:

Aluminum, PC & Friendly material

Power Supply: Tridonic / DALI According to customer request

Mounting: Recessed

LED Type: Osram 2835 SMD

UGR<13



| Order code | Color Temperature | LED power |
|---------------------------|-------------------|-----------|
| NSL-LPLG2-60609-30W-3000K | 3000k | 30 Watt |
| NSL-LPLG2-60609-30W-4000K | 4000k | 30 Watt |
| NSL-LPLG2-60609-30W-5000K | 5000k | 30 Watt |
| NSL-LPLG2-60609-30W-6000K | 6000k | 30 Watt |

SPECIFICATIONS

MAIN SPECIFICATIONS (T=25C)

| ITEM | DESCRIPTION |
|-----------------------------|---|
| Input Voltage | 220 - 240VAC |
| Frequency | 50/ 60 Hz |
| LED Type | Osram 2835 SMD |
| Power | 30 W |
| Power supply | Tridonic Austriaa |
| Light fixture output lumen | 3600 Lm |
| CRI | >80% |
| LED Efficacy (Light source) | 120-130 Lm/W |
| Materials | Aluminum, PC, Glass & Friendly material |
| Power factor | > 95% |
| CCT | 3000K,4000K, 5000K, 6000K |
| Beam Angle | 160° |
| Life Time | >50,000 Hours |
| Operating Temperature | -20°C to +55°C |
| Storage Temperature | -40°C to +85°C |
| Certifications | CE, SELV, and ISO |
| Size | 595 * 595 * 20.85mm |
| Weight | 4.6 KG |
| Mounting | Recessed |
| IP Rating | IP20 |



LED PANEL 60609

NASSLI
LED LAMP

Product .: LED Panel 60609

Item No.: NSL-LPLG2-60609-30WATT-4000K

