

Manufacturing is a design practice that works alongside those with a passion for design and production

ANTIBACTERIAL PANEL LIGHT6060

IP 65 5Y WAR Watt 36-48 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

I deal for Hospitals and laboratuvar etc...

Feature

This LED panel with an antibacterial and air-purifying effect is available in a size of 59.5 x 59.5 cm This is done by circulating air in the room.

Many types of bacteria, viruses or fungi to be reduced.

For example, dangerous hospital germs (MRSA), H1N1 or SARS germs.

Product Details

Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Steel sheet with electrostatic powder coating
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed / Suspended / Surface
IP Rating	IP65
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
36W	595x595x90	3600
Order Code	NSL-PL-ANB-6060-36W-XXK-SMD-NS-IP65	
Order Code	NSL-PL-ANB-6060-36W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
40W	595x595x90	4000
Order Code	NSL-PL-ANB-6060-40W-XXK-SMD-NS-IP65	
Order Code	NSL-PL-ANB-6060-40W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
48W	595x595x90	4800
Order Code	NSL-PL-ANB-6060-48W-XXK-SMD-NS-IP65	
Order Code	NSL-PL-ANB-6060-48W-XXK-SMD-TD-XX-IP65	