

Manufacturing is a design practice that works alongside those with a passion for design and production

LED CYLINDER LIGHT

IP 65 5Y WAR Watt 10-40 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc

Feature

High cooling aluminum, 500 cm2, make it good even for hot areas.

High lumen Output
Power saving: as it replace the halogen, CFL, metal halide so it save between 50% to 90% of the consumed power.

We Have diffrent option(diffuser, Wide lens, Narrow lens) Frame colores (Black/Gray/White).

Product Details

Input Voltage	220 - 240 V AC
Frequency	50 / 60Hz
Power Factor	>90%
CCT	3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	140Lm/W
Power Supply	Tridonic / Nassli
LED Type	Citizen / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	30°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +80°C
Certifications	CE, SELV and ISO
Mounting	Suspended/Surface Mounted
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
10W	W160 H250	1400
Order Code	NSL-CY-10W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-10W-XX-COB-NS-IP65	

Power (Watt)	Dimensions	Lumen
15W	W160 H250	2100
Order Code	NSL-CY-15W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-15W-XX-COB-NS-IP65	

Power (Watt)	Dimensions	Lumen
20W	W160 H250	2800
Order Code	NSL-CY-20W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-20W-XX-COB-NS-IP65	

Power (Watt)	Dimensions	Lumen
25W	W160 H250	3500
Order Code	NSL-CY-25W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-25W-XX-COB-NS-IP65	

Power (Watt)	Dimensions	Lumen
30W	W160 H250	4200
Order Code	NSL-CY-30W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-30W-XX-COB-NS-IP65	

Power (Watt)	Dimensions	Lumen
40W	W160 H250	5600
Order Code	NSL-CY-40W-XX-COB-TD-XX-IP65	
Order Code	NSL-CY-40W-XX-COB-NS-IP65	