

Manufacturing is a design practice that works alongside those with a passion for design and production

LED DOWN LIGHT CRX V2

IP 20/65 5Y WAR Watt 5-35 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas, Kitchens and Corridor etc...

Feature

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

High power saving fixture, no decay and color temperature shift.

Can be dimmable (through direct control or via network).

Product Details

Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP20 / IP65
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
7W	W35 H95 Ø70	840
Order Code	NSL-CRX23-3-V2-N70-7W-XXK-SMD-NS-IP20	
Order Code	NSL-CRX23-3-V2-N70-7W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-CRX23-3-V2-N70-7W-XXK-SMD-NS-IP65	
Order Code	NSL-CRX23-3-V2-N70-7W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
10W	W35 H95 Ø70	1200
Order Code	NSL-CRX23-3-V2-N70-10W-XXK-SMD-NS-IP20	
Order Code	NSL-CRX23-3-V2-N70-10W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-CRX23-3-V2-N70-10W-XXK-SMD-NS-IP65	
Order Code	NSL-CRX23-3-V2-N70-10W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
20W	W42 H169 Ø150	2400
Order Code	NSL-CRX26-3-V2-N150-20W-XXK-SMD-NS-IP20	
Order Code	NSL-CRX26-3-V2-N150-20W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-CRX26-3-V2-N150-20W-XXK-SMD-NS-IP65	
Order Code	NSL-CRX26-3-V2-N150-20W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
30W	W42 H218 Ø200	3600
Order Code	NSL-CRX28-3-V2-N200-30W-XXK-SMD-NS-IP20	
Order Code	NSL-CRX28-3-V2-N200-30W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-CRX28-3-V2-N200-30W-XXK-SMD-NS-IP65	
Order Code	NSL-CRX28-3-V2-N200-30W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
35W	W42 H218 Ø200	4200
Order Code	NSL-CRX28-3-V2-N200-35W-XXK-SMD-NS-IP20	
Order Code	NSL-CRX28-3-V2-N200-35W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-CRX28-3-V2-N200-35W-XXK-SMD-NS-IP65	
Order Code	NSL-CRX28-3-V2-N200-35W-XXK-SMD-TD-XX-IP65	