

Manufacturing is a design practice that works alongside those with a passion for design and production

LED FLOOD LIGHT-T

IP 65 5Y WAR Watt 50-200 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

Ideal for any large area with height ceiling.

Such as, warwhouse, factories, closed parks, commercial complexes, indoor playgrounds, hangars.

Feature

High cooling aluminum, with zip technology and 3D cooling created air convection channel, make it ideal for hot area.

High lumen output. High power saving fixture.

Overload protection, short circuit protection, and no-load protection.

Product Details

Input Voltage	220 - 240 V A C
Frequency	50/60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Philips
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	143° x 67°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted/ with Base
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
50W	L290 W190 H55	5500
Order Code	NSL-FLT-50W-XXK-SMD-NS-IP65	
Order Code	NSL-FLT-50W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
100W	L415 W235 H90	11000
Order Code	NSL-FLT-100W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-FLT-100W-XXK-SMD-PH-XX-IP65	

Power (Watt)	Dimensions	Lumen
150W	L555 W310 H95	16500
Order Code	NSL-FLT-150W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-FLT-150W-XXK-SMD-PH-XX-IP65	

Power (Watt)	Dimensions	Lumen
200W	L555 W310 H95	22000
Order Code	NSL-FLT-200W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-FLT-200W-XXK-SMD-PH-XX-IP65	