

Manufacturing is a design practice that works alongside those with a passion for design and production

LED HIGH BAY T

IP 65 5Y WAR Watt 60-100 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

Ideal for any large area with height ceiling.

Such as, warehouse, factories, closed parks, commercial complexes, indoor playgrounds, hangars

Feature

High cooling aluminum, with zip technology and 3D cooling created air convection channel, make it ideal for hot area.

High lumen output.

High power saving fixture.

Overload protection, short circuit protection, and no-load protection.

Product Details

Input Voltage	220 - 240 V A C
Frequency	50/60Hz
Power Factor	>95%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
Power Supply	Nassli / Philips
LED Type	Bridgelux High Power / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	60°, 90°, 120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended
IP Rating	IP65
Dimmable	On Request
Emergency	N/A
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
100W	D 300 H 188	11000
Order Code	NSL-HBT-XXD-100W-XXK-SMD-PH-XX-IP65	
Order Code	NSL-HBT-XXD-100W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-HBT-XXD-100W-XXK-SMD-NS-IP65	

Power (Watt)	Dimensions	Lumen
60W	D 300 H 188	6600
Order Code	NSL-HBT-XXD-60W-XXK-SMD-TR-CN-IP65	
Order Code	NSL-HBT-XXD-60W-XXK-SMD-NS-IP65	