
68

 $\textbf{Manufacturing} \ is \ a \ design \ practice \ that \ works \ along side$ those with a passion for design and **production** 

## LED LINEAR

20/40

**50,000** HOURS



 $\textbf{Manufacturing} \ is \ a \ design \ practice \ that \ works \ along side$ those with a passion for design and **production** 







## **Application**

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor.

## **Feature**

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

Do not cause any flickering and electromagnetic interference.

High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.

## **Product Details**

Input Voltage	24 VDC
Frequency	0 Hz
ССТ	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Nassli
LED Type	Osram
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended/Suspended
IP Rating	IP20 / IP40
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions Lumen
15W	W19 H20 1800
Order Code	NSL-LLS-19x20x1000-CV24-15W/M-XXK-SMD-NS-IP20
Order Code	NSL-LLS-19x20x1000-CV24-15W/M-XXK-SMD-TD-XX-IP20
Order Code	NSL-LLS-19x20x1000-CV24-15W/M-XXK-SMD-NS-IP40
Order Code	NSL-LLS-19x20x1000-CV24-15W/M-XXK-SMD-TD-XX-IP40