

Manufacturing is a design practice that works alongside those with a passion for design and production

LED LINEAR LIGHT OUTDOOR

IP 65 5Y WAR Watt 20-30 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor.

Feature

LED Linear Light designed for Harsh and hot environments, High lumen output.

Power saving as it replace the sodium metal halide so it it save between 5% to 75% of the consumed power.

Unlimited number of on/off switching cycles, Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and ant-aging fixture.

Over temperature protection, overload protection short circuit protection and no load protection.

Product Details

Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power Factor	>90%
CCT	3000K, 4000K, 5000K, 6000k, RGB
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	155°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Suspended, Surface Mounted
IP Rating	IP65
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
20W/m	L100 W75	2000
Order Code	NSL-LWP-84-74-1274-CV-20W-XXK-SMD-NS-IP65	

Power (Watt)	Dimensions	Lumen
30W/m	L100 W75	3000
Order Code	NSL-LWP-84-74-1274-CV-30W-XXK-SMD-NS-IP65	

Power (Watt)	Dimensions	Lumen
20W/m	L100 W75	2000
Order Code	NSL-LWP-84-74-1274-CC-20W-XXK-SMD-TD-XX-IP65	

Power (Watt)	Dimensions	Lumen
24W/m	L100 W75	2400
Order Code	NSL-LWP-84-74-1274-CC-20W-XXK-SMD-TD-XX-IP65	