

Manufacturing is a design practice that works alongside those with a passion for design and production

LED LINEAR SM

IP 20/40 5Y WAR Watt 10-15 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room, Theater, Cinemas, Kitchens and Corridor.

Feature

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

Do not cause any flickering and electromagnetic interference.

High power saving fixture, no decay and color temperature shift.

Mounting: Suspended, Recessed, Surface mounted.

Product Details

Input Voltage	24 VDC
Frequency	0 Hz
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	90°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Surface Mounted
IP Rating	IP20 / IP40
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
10W	W16 H16	1100
Order Code	NSL-LLS-16x16x1000-CV24-10W/M-XXK-SMD-NS-IP20	
Order Code	NSL-LLS-16x16x1000-CV24-10W/M-XXK-SMD-TD-XX-IP20	
Order Code	NSL-LLS-16x16x1000-CV24-10W/M-XXK-SMD-NS-IP40	
Order Code	NSL-LLS-16x16x1000-CV24-10W/M-XXK-SMD-TD-XX-IP40	

Power (Watt)	Dimensions	Lumen
15W	W16 H16	1650
Order Code	NSL-LLS-16x16x1000-CV24-15W/M-XXK-SMD-NS-IP20	
Order Code	NSL-LLS-16x16x1000-CV24-15W/M-XXK-SMD-TD-XX-IP20	
Order Code	NSL-LLS-16x16x1000-CV24-15W/M-XXK-SMD-NS-IP40	
Order Code	NSL-LLS-16x16x1000-CV24-15W/M-XXK-SMD-TD-XX-IP40	