

Manufacturing is a design practice that works alongside those with a passion for design and production

LED TRACK LIGHT

IP 20 5Y WAR Watt 15-30 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for decoration, shopping malls, Palaces, Trade shows, Supermarkets, Conference Halls, Hotels, Schools, Hospitals, Meeting room Factories, Theater, Cinemas and Corridor etc.

Feature

The most common form of track lighting still consists of straight pieces of track that are attached directly to the surface of the wall or ceiling.

They come with a piece that connects to a ceiling outlet, special 90-degree pieces for making turns, couplers to join two straight pieces together, and a “dead end” to safely cap the track at its end, but there are also curved or wave track fixtures as well as ones that are suspended below the ceiling.

Product Details

Input Voltage	220 - 240 V AC
Frequency	50 / 60Hz
Power Factor	>95%
CCT	2700k,3300k,4000k, 5000k,6000k
CRI	>80%
LED Efficiency	85-95lm/W
Power Supply	Tridonic / Nassli
LED Type	Citizen / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	10° - 60°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +80°C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted, Suspended
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
15W	W49 L127	1425
Order Code	NSL-TL-134-T3-15W-XXK-TD-XX-IP20	
Order Code	NSL-TL-134-T3-15W-XXK-NS-IP20	

Power (Watt)	Dimensions	Lumen
25W	W49 L127	2375
Order Code	NSL-TL-134-T3-25W-XXK-TD-XX-IP20	
Order Code	NSL-TL-134-T3-25W-XXK-NS-IP20	

Power (Watt)	Dimensions	Lumen
30W	W49 L127	2850
Order Code	NSL-TL-134-T3-30W-XXK-TD-XX-IP20	
Order Code	NSL-TL-134-T3-30W-XXK-NS-IP20	