

Manufacturing is a design practice that works alongside those with a passion for design and production

LED LIGHT UNDER CANOPY S

IP 65 5Y WAR Watt 50-150 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

Ideal for Gas Station, Factory, Industrial Area, Shopping Center, Green House, Football field, Car Park, Warehouse, General Lighting etc.

Feature

Fixture designed for Harsh and hot environments.

High lumen output. Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and anti-aging fixture.

Over temperature protection, Overload protection, Short-circuit protection, and No-load protection.

Product Details

Input Voltage	220 - 240 V A C
Frequency	50/60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Philips
LED Type	Osram / Philips
Materials	Aluminum, PC, & Friendly material
Beam Angle	85° / 147°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Certifications	CE, SELV and ISO
Mounting	Recessed
IP Rating	IP65
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
50W	L 285 W 95	5500
Order Code	NSL-UCAN-V1-50W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-UCAN-V1-50W-XXK-SMD-PH-XX-IP65	

Power (Watt)	Dimensions	Lumen
100W	L 290 W 190	11000
Order Code	NSL-UCAN-V1-100W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-UCAN-V1-100W-XXK-SMD-PH-XX-IP65	

Power (Watt)	Dimensions	Lumen
150W	L 290 W 278	16500
Order Code	NSL-UCAN-V1-150W-XXK-SMD-TD-XX-IP65	
Order Code	NSL-UCAN-V1-150W-XXK-SMD-PH-XX-IP65	