LED WALL MOUNTED LIGHT

Data Sheet Documents

IP
65

5Y
WAR

CRI
80% - 90%

50.000
HOURS





01	ORDER CODE	• NSL-WML-320-20W-XXK-SMD-NS-IP65
02	DIMENSIONS(MM)	• 320X230X190 MM
01	ORDER CODE	• NSL-WML-320-30W-XXK-SMD-NS-IP65
02	DIMENSIONS(MM)	• 320X230X190 MM
01	ORDER CODE	• NSL-WML-320-50W-XXK-SMD-NS-IP65
02	DIMENSIONS(MM)	• 320X230X190 MM
01	ORDER CODE	• NSL-WML-320-50W-XXK-SMD-TD-XX-IP65
02	DIMENSIONS(MM)	• 320X230X190 MM

03 GENERAL PRODUCT DESCRIPTION

Rugged LED wall pack light with a durable Aluminum housing and IP65-rated weatherproof build for reliable outdoor performance. Delivering wide-angle illumination with CRI >80,90 for crisp visibility,it's rated for 50,000 hours of dependable operation. Backed by a 5-year warranty, it's ideal for building perimeters, entrances, walkways,and security lighting. LED Wall Mounted Light is designed for Whether for a new building or renovation of an existing space, customers want lighting solutions that

04 FEATURES

provide quality of light and substantial energy and maintenance savings. The new CoreLine Wall-mounted range of LED products can be used to replace traditional wall-mounted luminaires incorporating compact fluorescent lamps. The Process of selecting,installing, and maintaining is so easy it's a simple switch

05 TECHNICAL DATA

Input Voltage	220 - 240 V A C
Frequency	60 / 50 H z
Power factor	>90%
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 6000K
CRI	80% - 90%
Wattage	20W-30W-50W
LED Efficiency	120-140Lm/W
Lumen	2700LM/4000LM/6750Lm
Power supply	Nassli
LED Type	Osram / Lumileds
Materials	PC material
Beam Angle	60° 90° 120°
Life Time	>50,000 hours
Operating Temp	°20-C to °55+C
Storage Temp	°40-C to °85+C
Certifications	CE, SELV and ISO
Mounting	Wall Mounted
IP Rating	IP65
Dimmable	On&Off / Phase cut / 0-10V / Dali
Emergency	On Request
Warranty	5 Years

06 APPLICATIONS

It can be widely used for Palaces, Hotels, Parking, gardens, Street, Housing etc...

