

Manufacturing is a design practice that works alongside those with a passion for design and production

PANEL LIGHT 30120/60120

IP 20/40 5Y WAR Watt 40-70 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

I deal for Schools, Offices, universities, Malls, supermarkets, and special design for hotels and palaces. etc...

Feature

The product used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

No glare and no heat under the the fixture.

Available with all mounting options (recessed, suspended, surface mounted).

Product Details

Input Voltage	220 - 240 V A C
Frequency	50 / 60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 5000k, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Recessed/Suspended / Surface
IP Rating	P20 / IP 40
Dimmable:	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
40W	119x295x9	3520
Order Code	NSL-PL-V2-30120-40W-XXK-SMD-NS-IP20	
Order Code	NSL-PL-V2-30120-40W-XXK-SMD-NS-IP40	
Order Code	NSL-PL-V2-30120-40W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-PL-V2-30120-40W-XXK-SMD-TD-XX-IP40	

Power (Watt)	Dimensions	Lumen
70W	595x119x9	6160
Order Code	NSL-PL-V2-60120-70W-XXK-SMD-NS-IP20	
Order Code	NSL-PL-V2-60120-70W-XXK-SMD-NS-IP40	
Order Code	NSL-PL-V2-60120-70W-XXK-SMD-TD-XX-IP20	
Order Code	NSL-PL-V2-60120-70W-XXK-SMD-TD-XX-IP40	