NASSLI
LED LIGHTS

LED SPOT LIGHT

Data Sheet Documents

IP
20

5Y
WAR

CRI
80%-90%

50.000
HOURS







01	ORDER CODE	• NSL-SPL-MR16-50-7W-XXK-SMD-LENS-DON-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100
01	ORDER CODE	• NSL-SPL-MR16-50-7W-XXK-SMD-DIF-DON-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100
01	ORDER CODE	• NSL-SPL-E27-50-7W-XXK-SMD-LENS-DON-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100
01	ORDER CODE	• NSL-SPL-E27-50-7W-XXK-SMD-DIF-DON-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100
01	ORDER CODE	• NSL-SPL-GU3.5-50-7W-XXK-SMD-DIF-LENS-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100
01	ORDER CODE	• NSL-SPL-GU3.5-50-7W-XXK-SMD-DIF-DON-XX-IP20
02	DIMENSIONS(MM)	• W49.4 L100

03 GENERAL PRODUCT DESCRIPTION

High-performance LED spotlight bulb 7W, featuring a premium finned aluminum heat sink body that delivers exceptional thermal management for consistent brightness and extended LED lifespan far beyond conventional halogen replacements. IP20-rated, rated for 50,000 hours, and backed by a 5-year warranty.

04 FEATURES

The precision multi-LED array produces a crisp, focused beam with outstanding anti-glare performance and CRI >80 for vivid, true-to-life color rendering that makes every space, product, and surface look its absolute best.

05 TECHNICAL DATA

Input Voltage	220-240VAc
CCT	2700K, 3000K , 3500K , 4000K, 5000K , 6000K
CRI	80%-90%
Wattage	7W
Lumen	700 Lm
LED Type	LUMILEDS
Beam Angle	45°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	IN Frame
IP Rating	IP20
Dimmable	On&Off / Phase cut / 0-10V / Dali
Emergency	On Request
Warranty	5 Years

06 APPLICATIONS

Ideal for retail displays, galleries, hospitality spaces, residential accent lighting, and any interior

