

Manufacturing is a design practice that works alongside those with a passion for design and production

SURFACE MOUNTED

IP 20 5Y WAR Watt 20-30 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can used for Hotels, Government Buillding, offices, Meeting Room, Residensial Buillding (villas, palaces, apartment), Shcool collage and Univercity, Hospitals Super Markit.

Feature

The prouduct used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

High power saving fixture, no decay and color temperature shift.

Can be dimmable (through direct control or via network).

A motion Sensor can be added.

Product Details

Input Voltage	220 - 240 V AC
Frequency	50 / 60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Tridonic / Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Surface Mounted
IP Rating	IP20
Dimmable	On Request
Emergency	On Request
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
20W	W66 L225	2200
Order Code	NSL-SRT1-220-20W-XXK-SMD-NS-IP20	
Order Code	NSL-SRT1-220-20W-XXK-SMD-DON-IP20	
Order Code	NSL-SRT1-220-20W-XXK-SMD-TD-IP20	

Power (Watt)	Dimensions	Lumen
30W	W66 L225	3300
Order Code	NSL-SRT1-220-30W-XXK-SMD-NS-IP20	
Order Code	NSL-SRT1-220-30W-XXK-SMD-DON-IP20	
Order Code	NSL-SRT1-220-30W-XXK-SMD-TD-IP20	

Manufacturing is a design practice that works alongside those with a passion for design and production

SURFACE MOUNTED

IP 20 5Y WAR Watt 18-24 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can used for Hotels, Government Building, offices, Meeting Room, Residencial Building (villas, palaces, apartment), Shcool collage and Univercity, Hospitals Super Markit.

Feature

The proudct used as pure light source, using LED technology human and environment friendly, no PB, Hg nor UV.

High power saving fixture, no decay and color temperature shift.

Can be dimmable (through direct control or via network).

A motion Sensor can be added.

Product Details

Input Voltage	220 - 240 V AC
Frequency	50 / 60Hz
Power Factor	>98%
CCT	2700K, 3000K, 4000K, 6000K
CRI	>80%
LED Efficiency	120-130Lm/W
Power Supply	Nassli
LED Type	Osram / Bridgelux
Materials	Aluminum, PC, & Friendly material
Beam Angle	120°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +65°C
Certifications	CE, SELV and ISO
Mounting	Surface Mounted
IP Rating	IP20
Dimmable	On Request
Emergency	No
Warranty	5 Years

Power (Watt)	Dimensions	Lumen
18W	W55.5 L180.5	1980
Order Code	NSL-SRFV1-180-18W-XXK-SMD-NS-IP20	
Order Code	NSL-SRFV1-180-18 W-XXK-SMD-DON-IP20	

Power (Watt)	Dimensions	Lumen
24W	W55.5 L225	2640
Order Code	NSL-SRFV1-220-24W-XXK-SMD-NS-IP20	
Order Code	NSL-SRFV1-220-24W-XXK-SMD-DON-IP20	