

Manufacturing is a design practice that works alongside those with a passion for design and production

WATERPROOF LED TUBE

IP 65 5Y WAR Watt 60-150 CRI >80 50,000 HOURS



Manufacturing is a design practice that works alongside those with a passion for design and production



Application

It can be widely used for Trade Shows, Supermarkets, Schools, Hospitals, Factories, Car Parking, Airport, Corridor etc....

Feature

LED ceiling light: The LED diffuser light is mounted directly on the ceiling for plaster ceiling mounting.

The LED moisture-proof diffuser light is already completely wired for LED technology and does not have to be converted.

Operating temperature -20°C to 65°C, low heat generation:

Temperature heat sink >1h max. approx. 45°C Robust plastic housing and protection class IP65 prevent penetration of foreign bodies or dust as well as protection against water jets.

Product Details

Materials	Aluminum, PC, & Friendly material
Raw material	Polycarbonate
Beam Angle	160°
Life Time	>50,000 Hour
Operating Temp	-20°C to +55°C
Storage Temp	-40°C to +85°C
Mounting	Ceilling, Wall mounting
IP Rating	IP65
Mech. Impact Protection	IK07
Warranty	5 Years

Power (Watt)	Dimensions	IP Rating
T8-150cm	L1567 x W125 x H85	65
Order Code	NSL-WP-LTU-2x150-IP65	

Power (Watt)	Dimensions	IP Rating
T8-150cm	L1567 x W95 x H85	65
Order Code	NSL-WP-LTU-1x150-IP65	

Power (Watt)	Dimensions	IP Rating
T8-120cm	L1267 x W125 x H85	65
Order Code	NSL-WP-LTU-2x120-IP65	
Order Code	NSL-WP-LTU-1x120-IP65	

Power (Watt)	Dimensions	IP Rating
T8-60cm	L667 x W125 x H85	65
Order Code	NSL-WP-LTU-2x60-IP65	

Power (Watt)	Dimensions	IP Rating
T8-60cm	L667 x W95 x H85	65
Order Code	NSL-WP-LTU-1x60-IP65	